

Bodewes Supplier 1900 DWAT



Main particulars

Length over all		69.00	m
Length b.p.p.		65.40	m
Breadth mld.		15.85	m
Depth		7.20	m
Draught design	abt.	5.40	m
Deadweight	abt.	1350	mtons
Draught scantling	abt.	6.00	m
Deadweight	abt.	1900	mtons
Trail speed design draught		14.5	knots

General capacities

Bollard pull		150 – 180	ton
--------------	--	-----------	-----

Tank capacities

Fuel oil	abt.	1300	m ³
Potable water	abt.	530	m ³
Ballast / drill water	abt.	570	m ³
Liquid mud / brine	abt.	550	m ³
Dry bulk	abt.	220	m ³

Accommodation

For a crew of 10 persons and 5 passengers, each person has a single berth cabin. Complete accommodation with ventilation, heating and air-conditioning.

Classification

American Bureau of Shipping
✕ A1 (E) offshore support vessel, AH,
towing service
✕ AMS, ✕ ACCU

Propulsion

Main engine: 2 medium speed diesels
Output: 2x 3360 kW

Equipment

Bow thruster 2x 700 kW
Stern thruster 700 kW

Deckcrane

The ship will be equipped with one fixed deck crane 5 ton – 12 m and two small mobile deck cranes on the ships side.

Navigation equipment

Communication equipment acc. to GMDSS area A3

Werfkade 22, 9601 LG, Postbus 32, 9600 AA, HOOGEZAND, The Netherlands.
Tel.: +31 598 393131, Fax: +31 598 399609
E-mail: info@royalbodewes.com
Internet: www.royalbodewes.com

**ROYAL
BODEWES**
SINCE 1812